

General Details			Units	Inverter - Cooling Only
Nominal Performance Data	Capacity	TR (Nom.)		4.0
		Cooling	KW	13.5
	Btu/h		46,072	
	EER		w/w	2.87
Indoor Unit Specifications				
Indoor Model			Units	AB48KC1QRA
Electrical Parameters	Power supply		Ph/V/Hz	1Ph/220-240V/50Hz
Performance	Air flow	cfm (H/M/L/SL)	1059/941/765/647	
		m3/h (H/M/L/SL)	1800/1600/1300/1100	
	Sound pressure level (H/M/L)		dB(A)	52/49/46/43
Installation	External dimensions(W/D/H)		mm	840/840/246
	Shipping dimensions(W/D/H)		mm	990/990/310
	Net/Shipping weight		kg	36/41
	Wireless Controller		Standard	YL-HBS01
Panel	Panel Model			PB-950KB
	External dimensions(W/D/H)		mm	950/950/50
	Shipping dimensions(W/D/H)		mm	1000/1000/110
	Net/Shipping weight		kg	6.5/9
Outdoor Unit Specifications				
Outdoor Model			Units	1U48NC1QRB
Electrical Parameters	Power supply		Ph/V/Hz	3Ph/380-415V/50Hz
Performance	Air flow	cfm (H)	3235	
		m3/h (H)	5500	
	Sound Pressure Level		dB(A)	61
Installation	External Dimensions(W/D/H)		mm	965/370/950
	Shipping Dimensions(W/D/H)		mm	1050/485/1130
	Net/Shipping Weight		kg	78/90
	Compressor Type		-	Rotary
	Refrigerant Type		-	R-410a
	Refrigerant Liquid Pipe Size		mm	9.52
	Refrigerant Gas Pipe Size		mm	19.05
	Total Pipe Length		m	50
	Max. Pipe Length - Horizontal		m	30
	Max. Pipe Length - Vertical		m	20
Working Temp.	Cooling (Min-Max)		°C	18 ~ 60

Note: Due to our policy of innovations, some specification may be change without any prior information.