

## Convertible

AC382MFERA



### FEATURES & BENEFITS

- Flexible installation, both on the floor or ceiling are ok.
- Only 240mm thickness, suitable for limited spaces
- Large angle air supplying
- Automatic horizontal and vertical swing
- Reserved fresh air inlet

### PERFORMANCE

Indoor unit name:	Convertible	Rated heating capacity(kW):	12.5
Indoor unit model:	AC382MFERA	Heating input power(kW):	0.4
Type:	Convertible	Rated cooling conditions:	Indoor(°C DB/WB):27/19 Ambient(°C DB/WB):35/24
Rated cooling capacity(kW):	11.2	Rated heating conditions:	Indoor(°C DB/WB):20/14.5 Ambient(°C DB/WB):7/6
Sensible capacity(kW):	7.8	Rated piping length (m):	
Cooling input power(kW):	0.4	Rated height separation(m):	

### INDOOR UNIT DETAILS

Power supply(V/Hz/Ph):	220-230/50/60/1	Airflow rate (H/M/L)(m <sup>3</sup> /h):	2040/1820/1610
Power supply connections:	L,N, Ground	Moisture removal(m <sup>3</sup> /h):	
Min. circuit Amps MCA (A):	2.51	Gas pipe connection(mm):	Φ15.88
Max. fuse Amps MFA (A):	8.04	Liquid pipe connection(mm):	Φ9.52
Dimensions(H×W×D)(mm):	700×1580×240	Condensate connection(mm):	Φ25
Panel(H×W×D)(mm):	/	Sound pressure(H/M/L)(dBA):	46/42/38
Net weight(kg):	54	Sound power level(H/M/L)(dBA):	59/55/51
Panel weight(kg):	/	Ext. static pressure (Rated/Max)(Pa):	0/0

### DIMENSIONAL DRAWING

